

## Restraint Straps

Horizontal and vertical straps, designed to building regulation BS5268 Part 3 and other building standards, fixing to masonry walls when connecting timber floor and roof systems to the main structure.

These items are also available as Timber Frame Cavity Straps.



## Product

### HDMH/HLDMH Multi Holed Straps

30mm x 5.0mm multi-holed straps supplied in 100mm increments. 6mm holes at 25mm offset centres. Available straight, bent or twisted or in combinations as required in both galvanised (HDMH) and stainless steel (SHDMH).

#### Ordering:

When ordering straps please quote the overall girth from end to end of the strap including any bends or twists or both ie:

*1200mm x 28mm x 4.0mm bent at 100mm = a strap 1100mm long leg plus a 100mm bend.*

When ordering straps that are both bent and twisted ensure that you specify the distance of the twist from the bend.

## Performance

#### Tensile Load Capacity

**8000N**

#### Fixing:

Fix using either no. 12 x 50mm BZP wood screws or 75mm x 4.0mm galvanised nails – for stainless straps stainless fixing must be used.

Packed in bundles of 10

#### Safety Precautions

HDMH/SHDMH Heavy Duty Multi-Holed Restraint Straps are manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.