According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EVERBUILD GUN GRADE Expanding Foam

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

1.3 Details of the supplier of the safety data sheet

Company : Everbuild - A Sika Company

Site 41

**Knowsthorpe Way** 

Cross Green Industrial Estate

Leeds

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone num-: National Chemical Emergency Centre (NCEC)

24 Hour Emergency Telephone Number +44 870 190 6777 ber

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

H222: Extremely flammable aerosol. Aerosols, Category 1

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Effects on or via lactation H362: May cause harm to breast-fed children. H335: May cause respiratory irritation.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

Specific target organ toxicity - repeated

exposure, Category 2

Long-term (chronic) aquatic hazard, Cat-

egory 4

H373: May cause damage to organs through pro-

longed or repeated exposure if inhaled.

H413: May cause long lasting harmful effects to

aquatic life.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	: :	10 12/2/2000	
Signal word	:	Danger	V

Hazard statements	H222	Extremely flammable aerosol.
riazara staternents	11222	,
	H229	Pressurised container: May burst if heated.
	H315	Causes skin irritation.

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H413 May cause long lasting harmful effects to

aquatic life.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand. Keep out of reach of children.

**Prevention:** 

P102

P202 Do not handle until all safety precautions

have been read and understood.

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other igni-

tion source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust or mist.

P263 Avoid contact during pregnancy and while

nursing.

P271 Use only outdoors or in a well-ventilated ar-

ea.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Storage:

P405 Store locked up.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

### Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues alkanes, C14-17, chloro

### **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

#### 2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







# **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373  specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 10 - < 20
isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1; H220	>= 5 - < 10
alkanes, C14-17, chloro	85535-85-9 287-477-0 01-2119519269-33- XXXX	Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 ———————————————————————————————————	>= 5 - < 10
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1; H220	>= 2,5 - < 5
Reaction products of phosphoryl trichloride and methyloxirane	1244733-77-4 807-935-0 01-2119486772-26- XXXX	Acute Tox. 4; H302	>= 2,5 - < 5

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

Substances with a workp	lace exposure limit :		
dimethyl ether	115-10-6	Flam. Gas 1; H220	>= 5 - < 10
	204-065-8		
	01-2119472128-37-		
	XXXX		

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Print Date 20.01.2022 Version 3.0

Date of last issue: 03.07.2021

Suspected of causing cancer.

May cause harm to breast-fed children.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

## 4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** Treat symptomatically.

### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media Water spray jet

Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod: :

ucts

Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

Hydrogen cyanide (hydrocyanic acid)

Chlorine compounds

## 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

## 6.4 Reference to other sections

For personal protection see section 8.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic

discharges.

Handle in accordance with good industrial hygiene and safety Hygiene measures

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label

precautions. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
------------	---------	-------------------------------	---------------------------	---------

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	GB EH40	
	Further informa	ation: Capable of ca	f causing occupational asthma.		
		STEL	0,07 mg/m3 (NCO)	GB EH40	
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC	
	Further informa	ation: Indicative			
		TWA	400 ppm 766 mg/m3	GB EH40	
		STEL	500 ppm 958 mg/m3	GB EH40	

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## **Biological occupational exposure limits**

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT

### 8.2 Exposure controls

## **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers).

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Print Date 20.01.2022 Version 3.0

Date of last issue: 03.07.2021

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state aerosol Colour various

Boiling point/boiling range No data available

Flammability Extremely flammable aerosol.

Flash point Not applicable

Auto-ignition temperature No data available

Not applicable pΗ

substance/mixture reacts with water

**Viscosity** 

Viscosity, kinematic Not applicable

Vapour pressure 5100 hPa

Density ca. 0,95 g/cm3 (23 °C)

### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Not classified based on available information.

### **Components:**

## Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

### Reaction products of phosphoryl trichloride and methyloxirane:

Acute oral toxicity : LD50 Oral (Rat): > 630 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### **Components:**

#### alkanes, C14-17, chloro:

Assessment : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Causes serious eye irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

May cause harm to breast-fed children.

### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified based on available information.

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Product:**

### **Ecotoxicology Assessment**

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

#### Components:

## Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): > 1.640

Country GB 100000031534

11 / 18

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

plants mg/l

Exposure time: 72 h

alkanes, C14-17, chloro:

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic : 10

toxicity)

Reaction products of phosphoryl trichloride and methyloxirane:

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 82 mg/l

plants Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 13

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 32 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains components considered to

be either persistent, bioaccumulative and toxic (PBT), or very

persistent and very bioaccumulative (vPvB)...

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

May cause long lasting harmful effects to aquatic life.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

wav.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 16 05 04\* gases in pressure containers (including halons)

containing dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

### 14.1 UN number

ADR : UN 1950 IMDG : UN 1950 IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

**ADR** : 2 **IMDG** : 2.1

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

**IATA** : 2.1

## 14.4 Packing group

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

Remarks : Transport according to chapter 3.4 (LQ) possible

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

#### 14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Diphenylmethanediisocyanate, isomeres and homologues (Number on

list 74, 56)

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

alkanes, C14-17, chloro

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

**REACH Information:** 

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us. and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 23,07% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 23,07% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758





## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

### Other regulations:

75/324/EEC

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H220 : Extremely flammable gas.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H362 : May cause harm to breast-fed children.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Lact. : Effects on or via lactation
Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







## **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

**ADR** European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS Chemical Abstracts Service Derived no-effect level DNEL

Half maximal effective concentration EC50

**GHS** Globally Harmonized System

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG** 

LD50 Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

**MARPOL** International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

**OEL** Occupational Exposure Limit

**PBT** Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

**REACH** Regulation (EC) No 1907/2006 of the European Parliament

> and of the Council of 18 December 2006 concerning the Registration. Evaluation. Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

**SVHC** Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

#### **Further information**

#### Classification of the mixture: Classification procedure:

Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
Lact.	H362	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 4	H413	Based on product data or assessment

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758







# **EVERBUILD GUN GRADE Expanding Foam**

Revision Date: 20.01.2022 Version 3.0 Print Date 20.01.2022

Date of last issue: 03.07.2021

Filename: Rehsfil0.WWI

P:\Public\Safety\Safety Data Sheets\Suppliers\Incorez (Production) Directory:

Template:

EHS\_L\_TEXT(CED-U00 Title:

Subject:

Author: Mandy

Keywords: Comments:

Creation Date: 20/01/2022 11:55:00

Change Number:

Last Saved On: 20/01/2022 11:55:00

Last Saved By:

Total Editing Time:
Last Printed On: 0 Minutes

As of Last Complete Printing

Number of Pages: 18 Number of Words: 8,890 (approx.)

Number of Characters: 50,674 (approx.)