



END type angle brackets have been completely redesigned for greater versatility in their applications.

## FEATURES



INDOOR




Z275

## Material

- Galvanized steel S250GD + Z275 according to NF EN 10346.

## Benefits

- Wide variety of uses.
- Wood to wood or wood to concrete.
- Oblong slot for simpler alignment and adjustment.



## APPLICATIONS

### Header member




- Supporting member:** wood, concrete, steel, etc.
- Supported member:** PVC, wood, aluminium, steel joinery, etc.

### For Use With

- Fastening of interior and exterior joinery, etc.

## TECHNICAL DATA

### Dimensions and Allowable values



References	Dimensions and drill holes [mm]				Holes Flange A		Holes Flange B	
	A	B	C	t	Ø6.5	Obround	Ø9	Obround
END55/1,5C50	55	71.5	30	1.5	-	1 x Ø9x20	1	1 x Ø6.5x30
END100/1,5C50	100	71.5	30	1.5	2	1 x Ø9x20	1	1 x Ø6.5x45

## INSTALLATION

### Fixing

#### On wood:

- CNA annular ring-shank nails 4.0 mm.
- CSA screw 5.0 mm.

#### On concrete:


- HIPC 8-60/20 drive anchors.

#### On metal:


- Bolts dia. 8 mm.

### Installation

- Use appropriate screws.



Timber to  
masonry  
connection



Timber to  
masonry  
connection