FUHR Door Locks 856 Type 3, Type 1 & Type 2

- Reversible latch and deadbolt
- Variable handle height supplied at 1020mm
- FUHR silver corrosion resistant surface finish
- Profile related locking plates
- Lever operated door locks

FUHR multisafe multipoint door locks are renowned for their ease of use, reliability and durability. Profile specific keeps ensure secure fastening to the outer frame. Lever/Lever action is a very simple means of operating a door lock – when the door is unlocked by the cylinder, depress the lever to release all locking points. On closing, lift the lever to engage the main locking points then turn the key in the profile cylinder to throw the central deadbolt and to deadlock all other locking points.

Where security is a greater concern on main residential doors, the Secured by Design accredited FUHR 856 Type 3 lock, with 2 hook bolts and two roller cams is recommended. The hooks engage into pressed steel locking keeps - profile related to fit the profile securely. The Type 3 door lock has also achieved a half hour fire rating on a tested door set.

Technical Information:

- Faceplate: 16mm x 3mm Deadbolt: 20mm*
- Backset options:
 - 25, 30, 35 and 45mm
- PZ centre: 92mm
- Spindle size: 8mm
- Clearance required behind backset: 18mm

Throw

- Hook bolt: 20mm
- Roller cam adjustment: +/- 0.8mm
- *14mm on 25mm and 30mm backset options











