

TECHNICAL SPECIFICATION SHEET

ZCS030LL



| CODE | FINISH |
|-------------------|-----------------|
| ZCS030LLSS | SATIN STAINLESS |

SPECIFICATIONS

- Rose diameter 52mm
- Rose projection 8mm
- 19mm diameter tubular lever
- ZCS 304 Grade material
- Push on stainless steel outer rose
- M4 male / female fixings supplied
- 100mm Heso steel spindle supplied
- M6 Heso grub screws for additional fixing strength
- Also supplied with 20mm wood screws
- Fire tested suitable For 30 & 60 min timber doors
- Complies to the design requirements of BS8300
- Suitable for 35-54mm doors

FOR USE WITH

- ZDL7260LLSS
- ZDL7260RLSS


STANDARDS



SUITABILITY



TECHNICAL



| CODE | DESCRIPTION | FINISH | ADDITIONAL INFO. |
|---|---------------------------------------|--|---------------------|
| ZCS030LLSS | RTD lift to lock lever – push on rose | SS | SS304 lever on rose |
|  <p>For more information please contact us today: Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk</p> <p>ZOO Hardware Ltd, Unit B, Dukes Drive Kingmoor Park North, Carlisle, Cumbria CA6 4SH</p> | |  <p>URS is a member of Registrar of Standards (Holdings) Ltd.</p> | |