

LKX



Models: 1515 LP/
2015 LP

MORE INFO



CHARACTERISTICS

- 4 poles electrical motor (1400 rpm) with thermal protection and water cooling (three phase models).
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery Stainless steel valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank (3 lt) for indirect suction.
- Auxiliary motor for burner.
- Heavy duty steel frame.
- Hose reel with brake **(optional)**.

TECHNICAL DATA

	LKX 1310 LP	LKX 1515 LP	LKX 2015 LP
code	36072-00167	36072-00159	36072-00160
rated/max pressure	110/150 bar - 1595/2175 psi	150/180 bar - 2175/2610 psi	200/230 bar - 2900/3335 psi
max delivery flow rate	660 l/h - 2.91 gpm	900 l/h - 3.96 gpm	900 l/h - 3.96 gpm
abs. power/supply	3000 W/230V 1~50Hz	5500 W/400V 3~50Hz	7300 W/400V 3~50Hz
motor power	2,2 kW	4,0 kW	5,5 kW
pump model	MP3/1400 rpm	MPW3.5/1400 rpm	MPW3.5/1400 rpm
T max water inlet/outlet	40/110 °C	40/110 °C	40/110 °C
dimension (cm)/weight	94x65x90/112 Kg (246 lbs)	94x65x90/125 Kg (275 lbs)	94x65x90/128 Kg (282 lbs)

PLUS



4 twinned solid wheels to facilitate movement on any type of surface



Optional hose reel kit (max 30 meters of high pressure hose)



Side supports for gun and lance housing







Professional motor pump with 4-pole motor (1400 rpm) and self-priming linear pump: the low rotation speed significantly extends the life of the components inside the motor pump, guaranteeing greater efficiency and silence

Other available versions:

- 36072-00165 LKX 2015 with header tank
- 36072-00184 LKX 2015 with header tank and antiscaling device

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-01695 Gun M22 - 3/8 with rotating coupling 	 <ul style="list-style-type: none"> • 00080-01715 Lance M22 high/low pressure 	 <ul style="list-style-type: none"> • 00080-03188 Nozzle type 045 (mod. 1310/2015) • 00080-03191 Nozzle type 060 (mod. 1515) 	 <ul style="list-style-type: none"> • 00080-02347 High pressure hose 10 m 	
--	---	---	--	--

OPTIONAL

<ul style="list-style-type: none"> • 10001-13221 Hose reel with brake (hose not included) 	<ul style="list-style-type: none"> • On request models with header tank and/or antiscaling device. 	<ul style="list-style-type: none"> • 00073-00114 Antiscaling LC-PRECAL (pcs. 4 x 5 lt.) 	<ul style="list-style-type: none"> • Turbo Lance code: 00080-02966 - (mod. 1310/2015) 00080-02967 - (mod. 1515) 	<ul style="list-style-type: none"> • High pressure hose code: 00080-02258 10 m - 310 bar 00080-02261 20 m - 400 bar 00080-02264 10 m R2 00080-02262 20 m - 400 bar 00080-02263 10 m - 400 bar food industry (mod.2015)
<ul style="list-style-type: none"> • Sandblasting lance code: 00080-02957 (mod. 1310/2015) 00080-02958 (mod. 1515) 				